



OGA DIAGONAL: 20.46 [519.68]
VA DIAGONAL: 19.74 [501.35]
PA DIAGONAL: 18.61 [472.61]

ESD CLAMSHELL
CASE
IS USED WITH ALL
NOV, USB AND SER
TERMINATIONS.

(SER)
EXII-7720SC
98-0003-2217-6
SERIAL CONTROLLER
SOLDER SIDE

(USB R)
EXII-7760UC
98-0003-2814-0
USB CONTROLLER
SOLDER SIDE

(FFC)



NOTES:

1. WEIGHT OF GLASS IN GRAMS: 1008±10%
2. 5 PIN AMP CONNECTOR
LATCH STYLE HOUSING P/N: 487526-4
TIN CONTACTS P/N: 2-487406-4
HOUSING ORIENTED WITH LATCH DOWN

PINOUT	
1	LR
2	LL
3	SHLD
4	UL
5	UR

UNITS INCHES [MM]

TOLERANCES
UNLESS OTHERWISE SPECIFIED
.X ±
.XX ±.03 [.76]
.XXX ±.015 [.38]
ANGLES ±1°



DO NOT SCALE DRAWING

SCALE 1 = 1



3M TOUCH SYSTEMS
METHUEN, MA
USA
© COPYRIGHT 2004
THIS DOCUMENT IS COPYRIGHTED PROPERTY OF THE
3M COMPANY AND MAY NOT BE REPRODUCED
WITHOUT 3M WRITTEN PERMISSION OR USED OR
DISCLOSED FOR OTHER THAN 3M AUTHORIZED
PURPOSES.

DRAWN K.CROWLEY 9/05

06	REVISED PER CO 030452	5/09	SB
05	REVISED PER CO 030107	3/09	MTD
04	REVISED PER CO 028687	4/08	AM
REV	CHANGE NOTICE	DATE	DRW

TITLE MARKETING DRAWING SCT32NN 19.74"			
SIZE C	DOCUMENT NO. 28364-MKT	SHEET 1 OF 1	REV 06